

# microshield *plus*



## Multi-Purpose cleaner for walls and floors

### DESCRIPTION

Multi-purpose, wall and floor alkaline tile cleaner for all types of ceramic, natural stone, wood and laminate floor surfaces.

### Use for

- General showers, kitchens and bathrooms
- Cleaning all types of floor and wall surfaces including:
  - Ceramics
  - Marble
  - Natural stone
  - Slate
  - Terrazzo
  - Glass
  - Stainless Steel
  - Wood\* (i.e. wood finishes)
  - Laminate Floors\*
  - UPVC
  - Vinyl Tiles / Sheets
  -

\*Ensure non-moisture sensitive backing.

### PRODUCT INFORMATION

**Composition:** Alkaline liquid, special formulation.

**Colours:** Colourless.

**Pack sizes:** 750ml

### Key Features:

- Fast-acting formula removing grease, dirt and stains.
- Restores appearance of existing grouts in tiling.
- Extra hygiene protection.
- Use on walls and floors.
- Ideal for use with wood finishes and laminate floors.
- Ideal for use with general cleaning and stainless steel.

### Restrictions: NOT suitable for

- Moisture sensitive materials and backings.

### USAGE & SERVICE CONDITIONS

|          |   |          |   |
|----------|---|----------|---|
| Walls    | ✓ | Floor    | ✓ |
| Interior | ✓ | Exterior | ✓ |
| Dry      | ✓ | Wet      | ✓ |
| Worktops | ✓ |          |   |

(1) Ensure non-moisture sensitive backing.

### SURFACES

|                     |   |
|---------------------|---|
| Stainless Steel     | ✓ |
| Glazed ceramics     | ✓ |
| Marble              | ✓ |
| Hard natural stone  | ✓ |
| Slate               | ✓ |
| Terrazzo            | ✓ |
| Glass               | ✓ |
| Wood (1)            | ✓ |
| Laminate Floors (1) | ✓ |
| UPVC                | ✓ |
| Vinyl Tiles/Sheets  | ✓ |

### USAGE: COVERAGE

|              |                       |
|--------------|-----------------------|
| Area         | Coverage              |
| Wall & Floor | 20 - 40m <sup>2</sup> |

### APPLICATION

1. Direct nozzle towards surface and spray a light film.
2. Wipe with clean cloth.
3. If more heavily stained, wait 1-2 minutes before

**HEALTH & SAFETY INFORMATION / GOOD PRACTICE ADVICE**

For detailed information and safety guidance, please refer to Product Material Safety Data Sheet [MSDS].

**TECHNICAL ADVISORY SERVICE**

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

**POWERSPEC**

A unique computerised online specification system for the design and installation of ceramic, mosaic and natural stone tiling.

Visit [www.powerspeconline.com](http://www.powerspeconline.com)

**SHELF LIFE**

12 months under normal dry conditions. Protect from frost and damp.

**QUALITY AND ENVIRONMENTAL STANDARDS**

Manufacturing quality assurance standards conform to BS EN ISO 9001. Satisfies the environmental management requirements and operational scope of ISO 14001.

**CONDITIONS OF SALE**

Sold subject to the Company's Conditions of Sale. *Available on request.*

*For sales and technical queries, contact:*

**BUILDING ADHESIVES LTD**

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB, England  
[www.bal-adhesives.com](http://www.bal-adhesives.com)

Sales

Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical

Tel: +44 (0) 1782 591120 or

+44 (0) 845 600 1 222

Fax: +44 (0) 1782 591121

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.