

**DECLARATION OF PERFORMANCE**  
**In accordance with annex III of Regulation (EU) 305/2011**  
**(Construction Products Regulation)**  
**Amended by Commission Delegated Regulation (EU) No 574/2014**  
**For the product BAL Easyoxy AG**  
**No. BAL057-CPR/2013**

1. Unique identification code of the product-type:

**EN 12004:R2**

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Improved reaction resin adhesive**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

**Building Adhesives Limited,  
Newstead Industrial Estate,  
Longton Road,  
Trentham,  
Stoke on Trent,  
Staffordshire,  
ST4 8JB**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

6. (a) In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN 12004:2007+A1:2012**

**The Notified Body 1212 carried out the determination of the product type on the basis of type testing on samples provided on behalf of Building Adhesives Limited under System 3.  
Reaction to fire performance has been declared in accordance with the Commission Decision of 9<sup>th</sup> February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.**

- 6 (b) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:


**Not applicable**

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007 +A1:2012
Bond strength as: - initial shear adhesion strength	$\geq 2.0\text{Nmm}^{-2}$	
Durability for; - shear adhesion strength after water immersion - shear adhesion strength after thermal shock	$\geq 2.0\text{Nmm}^{-2}$ $\geq 2.0\text{Nmm}^{-2}$	
Release of dangerous substances	See MSDS	

8. The performance of the product identified above is in conformity with the declared performances.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by: David Longwell – Technical Manager



Stoke on Trent 22/04/16